VT 10 L
camera system
brochure

VT 10 L inspection camera

Extremely compact, watertight color camera with integrated LED lighting and an outer diameter of 10 mm

Applications

- Pipe, sewer inspection
- Underwater inspection
- Remote operated manipulators
- Retrieval of foreign objects
- Hard to reach areas
- Industry
- Nuclear facilities

Features

- Small and robust design in stainless steel
- Outer diameter of 10 mm
- PAL/NTSC
- Integrated LED lighting
- Water tight up to 10 m



Technical specifications - VT 10 L camera

This document is for general information only, please consult the system manual for detailed specifications

Housing	stainless steel
Image sensor / number of effective pixels	1/4" Color CCIQ
Horizontal resolution	400 TVL
Signal system	PAL/NTSC
Minimum illumination	0.1 lx
Optical zoom	n/a
Digital zoom	n/a
Focus	fixed
FOV	---
Minimum object distance	---
Video output	---
Range - PAN	n/a
Range - TILT	n/a
Lighting	8x LED
Luminous flux	~ 38.4 lm
Dimension (ø x L)	10x37.5 mm
Weight	0.057 kg
Operating temperature	---
Water tight / water depth	1 bar / 10 m
Radiation tolerant	---
Total dose	---
Optionals	---
Features	---

*unit in mm





DACON Inspection Technology
+31(0)71 - 747 0110
www.daconbv.nl
info@daconbv.nl
YOUR RELIABLE ADVISER AND PARTNER FOR VISUAL INSPECTION EQUIPMENT