



Ø 45 mm Visioprobe compact camera

Industrial endoscopy

- Pan & tilt camera
- Manual focus from 5 mm to infinity
- Wide depth of view
- 24 powerful LED
- Can be fixed on a telescopic pole
- Aluminium or stainless steel

Compatible with:



Control Unit

CAMERA Ø45mm - ALUMINIUM

Reference:	VP45A
Diameter:	45 mm
Length:	141 mm
Overall length:	152 mm
Weight:	0,45 Kg
Material:	Aluminum alloy colorless anodized
Sensor:	CMOS 1/4" 0,025 Lux - 480LTV Auto/manual shutter
Focal:	2,45 mm
Pan angle:	360°
Tilt angle:	- 110° → + 110°
Field of vision:	80°
Sharpness range:	from 5 mm to ∞ Remotely adjustable
Lighting:	24 LED High brightness
Protective window:	Saphir
Waterproofing:	2 bars
Temperature of use:	from -30° to +65°C

CAMERA Ø45mm - STAINLESS STEEL

Reference:	VP45X
Diameter:	45 mm
Length:	141 mm
Overall length:	152 mm
Weight:	0,94 Kg
Material:	Stainless steel 304L
Sensor:	CMOS 1/4" 0,025 Lux - 480LTV Auto/manual shutter
Focal:	2,45 mm
Pan angle:	360°
Tilt angle:	- 110° → + 110°
Field of vision:	80°
Sharpness range:	from 5 mm to ∞ Remotely adjustable
Lighting:	24 LED High brightness
Protective window:	Saphir
Waterproofing:	2 bars
Temperature of use:	from -30° to +65°C



Inspection
Technology

+31(0)71 - 747 0110
www.daconbv.nl
info@daconbv.nl

YOUR RELIABLE ADVISER AND PARTNER FOR VISUAL INSPECTION EQUIPMENT