

# mC360

**Your eyes are everywhere.**

Examine even the most remote angles? No problem - thanks to our Pan-and-Tilt Camera Head.

## Basic Configuration

- 130m/11.2mm Push Rod Cable
- Stainless Steel and Carbon Fibre Coiler
- Control Unit with function keys
- light regulation
- 50mm SK50 Color Pan-and-Tilt Camera Head
- For pipes starting at DN70 with diameters between 70 and 400mm
- Digitale Speicherung von Video und Standbild auf SD-Karte
- BNC-Video Out
- Internal Power Supply with 100 to 240V
- Two ND2054HD31 Li-Ion batteries (14.4 V, 3100 mAh)<sup>1</sup>
- 8" TFT LCD-Monitor (4:3-Format)
- Remote Control with funktion keys for Camera Head control
- Built-in and extremely strong locating coil with 512Hz and 33Hz

## Camera Head

### SK50

- 50mm SK50 Color Pan-and-Tilt Camera Head (visible Pan-and-Tilt angle 150°)
- endless rotation possible
- diagonal field of view of 106°
- auto-mechanically adjustable Focus
- digital Zoom
- Usable up to a minimum illumination of 0.02 LUX at F1.2
- Illumination using 6 Power-LEDs 80° as well as 4 Power-LEDs 150°
- intelligent Lightcontrol
- 1/3" CMOS Color Sensor (560 PAL/500NTSC)
- durable Sapphire Glas Camera Cover
- 6 bar pressureproof (up to 60 on demand)
- including a Transport Case with numerous Accessories, Tools and Spacers

## Connection

### Wireless connection (optional)

- via WIFI on Smartphones
- minCam-Viewer App for Tablets

### Wired connection

- via BNC cable connection and „Grabber“<sup>2</sup> on Netbooks or Notebooks
- via direct cable connection to our monitors TFT5R, TFT8R
- via BNC cable connection to MPR<sup>3</sup>

## Options/Compatibility

### Optional Accessories<sup>4</sup>

- WIFI-Set
- Text Generator

### Compatible Software

- WinCan
- POSM
- Viewline
- PipeCommander
- Pipex
- Haite K3000



<sup>1</sup> Operating time approx. 230-240 minutes (mC360 with SK50 at 50% illumination, recording mode on TFT8R and two batteries), charging time approx. 205 minutes  
<sup>2</sup> Analog Digital Video Converter    <sup>3</sup> Media Pocket Recorder    <sup>4</sup> Upgrades upon request only