

## mC50

**Simple. Lightweight. Effective.**

Comfortable inspections of pipes with diameters from 32 and up to 400mm.



# mC50

## Simple. Lightweight. Effective.

Comfortable inspections of pipes with diameters from 32 and up to 400mm.

Comfortably inspect pipes with diameters ranging from 70 to 400mm.

### Mono-Set

- 55mm KK55SL Color Axial Camera Head
- 60m/9.2mm Push Rod Cable
- Suitable for pipes starting at DN65
- up to 10 bar pressureproof

### Duo-Set

like Mono-Version but additionally with:

- 29mm KK29SL Color Axial Camera Head
- 20m/6.7mm Push Rod Cable
- Suitable for pipes starting at DN40
- up to 10 bar pressureproof

### Specifications (Mono-Set)

- Suitable for pipes with diameters between 70 to 400mm
- 60m/9.2mm Push Rod Cable
- Color Axial Camera Head with 55mm diameter and permanent upright image/self-leveling
- Stainless Steel and Carbon Fiber Coiler
- Control Unit with Function Keys
- Infinitely variable Light Regulation
- BNC Video Out
- Internal Power Supply with 100 to 240V
- Available as Mono or Duo Set (2 Camera Heads and Push Rod Cables)

## Output

### Wired Connection

- Via BNC cable connection and „Grabber“ (Analog Digital Video Converter) on Netbooks or Notebooks
- via direct cable connection to our monitors TFT5R, TFT8R, PC101
- Via BNC cable connection to MPR (Media Pocket Recorder)

### Compatible Software

- WinCan
- PipeCommander
- POSM
- Pipex
- Viewline
- Haite K3000

